

HATCRETE

Technical Data - Water Based Self-Compacting Concrete Curing Agent



(90.41) E (G)

PRODUCT DESCRIPTION

PICS Water Based Self-Compacting Concrete Curing Agent is a water based acrylic emulsion.

PURPOSE

PICS Water Based Self-Compacting Concrete Curing Agent can be applied to aid curing of freshly laid self-compacting concrete.

SPECIAL PROPERTIES

- Aids curing of fresh self-compacting concrete
- Slows surface drying
- Reduces chances of plastic cracking
- Suitable for interior or exterior use
- 84% curing efficiency
- Conforms with ASTM C-309 and ASTM C-156
- Leaves an acrylic, non waxy membrane

APPLICATION INSTRUCTIONS

Mix well, or shake container thoroughly before use.

As soon as final finish is completed and the concrete surface is free of any bleed water, the product should be applied by sprayer as soon as the surface has gained sufficient strength to withstand spray application without damage.

The product must be applied at a MINIMUM of 5m²/ litre in one or two applications. Allow first coat to dry tack free prior to applying second coat (if required). Application rates may increase due to surface porosity, surface profile and uniformity of application.

PACKAGING

10 and 25 litre containers.

STORAGE

Store at minimum 5°C. Do not allow to freeze.

CURING EFFICIENCY

Independently tested to BS7542:1992 guidelines with dry shake hardener added and trowelled into the surface and final finish trowelled. After 72 hours in the drying cabinet, in the sprayed specimen 84% of the moisture in the mortar that was available to evaporate had been retained.

SPECIFICATION CLAUSE

*"Freshly laid concrete, which has received its final finish shall be treated with **PICS Water Based Curing Agent** from PICS (Tel 01635 202224) to aid curing of the finished floor. All materials should comply to ISO9001 for Quality Assurance. All work should be carried out in conjunction with the manufacturer's current technical data sheet and instructions for use".*

HEALTH AND SAFETY

PICS Water Based Curing Agent is non-toxic and non-flammable. The curing agent can normally be applied without a vapour mask or safety glasses. Avoid contact with skin and eyes. Flush affected areas with water. Do not take internally. Refer to Health & Safety Data Sheet for further information.

TECHNICAL SERVICES

For further information, call our technical dept. on:-

☎ UK (01635) 202224
☎ International +44(0) 1635 202224

e-mail
Web Site

info@picsuk.com
www.picsuk.com

19-06-2019



MANUFACTURED BY:
PATTERN IMPRINTED CONCRETE SUPPLIES LIMITED

Unit 2, Red Shute Hill Ind. Est. Hermitage, Nr Newbury, Berkshire RG18 9QL

Tel: +44 (0) 1635 202224 e-mail: info@picsuk.com Web: www.picsuk.com