

Technical Data - Adcolour

13-03-2025



PRODUCT DESCRIPTION

HATCRETE Adcolour is a colouring additive for cementitious materials. It provides uniform streak free colour with minimal wash down of mixing equipment. **HATCRETE Adcolour** is stable in the presence of lime and sunlight and contains no chlorides. The product is available in 24 standard colours and custom colours are available to order. All the pigments used in the manufacture of **HATCRETE Adcolour** are UV stable, durable and conform to BS EN 128 78: 2014.

PACKAGING

HATCRETE Adcolour is normally supplied in 20kg bags and dosage rates are typically 1 % to 3% based on the cement content.

DOSAGE RATES

- Group 1 Colours 1% of the cement content
- Group 2 Colours 2% of the cement content
- Group 3 Colours 3% of the cement content
- Gabbro 3% of the cement content
- Everglade 2% of the cement content

HATCRETE Adcolour is ideally suited to pre-cast work.

STORAGE

Bags should be stored off the ground, unopened, in a dry environment.

APPLICATION

HATCRETE Adcolour is normally added to the batch mixer and should be used in mixes that contain non-reactive aggregates. To achieve best results ensure that all ingredients and working practices remain constant. **HATCRETE Adcolour** should ideally be added to the mixer when half the contents are batched. Never add to a totally empty mixer. Adequate mixing time should be allowed for the product to integrate but this should be no longer than normal. To achieve brighter colours use white cement. In all cases it is advisable to carry out trial mixes and prepare sample panels using the mixes, materials and methods envisaged for the final project, before work commences.

HANDLING, PLACING AND COMPACTION

Concrete treated with **HATCRETE Adcolour** should be utilised in the same way as high quality architectural concrete. The principles of good concrete practice must be maintained at every stage. The placing of coloured concrete in temperatures below 5°C should be avoided at all times.

CURING AND FINISHING

To reduce the risk of early age plastic shrinkage cracking due to rapid drying, the concrete should be cured using **HATCRETE Cure & Seal** (Either Solvent-based or Water-based). This will also minimise the likelihood of efflorescence. Please refer to Technical Data Sheet for further details. Accepted methods of curing ordinary uncoloured concrete including damp Hessian, sand, plastic sheeting or ponding **MUST NOT BE USED** as these may affect the final colour uniformity of the concrete.

HEALTH AND SAFETY

Care must be taken when handling, storing and using **HATCRETE Adcolour**. Before using **HATCRETE Adcolour** please read Safety Data Sheet available from HATCRETE.

TECHNICAL SERVICES

For further information, call our technical dept on:

UK (01635) 202224
International +44(0) 1635 202224

E-Mail: info@picsuk.com
Website: www.hatcrete.com

WARRANTY

Pattern Imprinted Concrete Supplies Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst Pattern Imprinted Concrete Supplies Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

MANUFACTURED BY PICS

Unit 2 & 4, Red Shute Hill Ind. Est. Hermitage, Nr Newbury
Berkshire RG18 9QL

Tel: +44 (0) 1635 202224 E-Mail: info@picsuk.com Web: www.hatcrete.com

