

Technical Data - Xylene Thinners

10/04/2025



PRODUCT DESCRIPTION

HATCRETE Xylene Thinners is a medium evaporating clear, colourless, aromatic solvent.

PURPOSE

HATCRETE Xylene Thinners is used to dissolve HATCRETE acrylic based coatings. It will dissolve or soften many types of paints, resins and adhesives, including acrylic based materials.

SPECIAL PROPERTIES

- Break down / dissolve solvent based acrylic curing agents
- Break down / dissolve solvent based acrylic sealers
- Remove blooming whiteness
- Cleaning tools and sprayers
- Used to remove sealers

APPLICATION INSTRUCTIONS

Can be applied using a Viton equipped pressure sprayer or by soft broom. Solvent based acrylics will be softened and melted within a few minutes. A little more product may be needed if removing acrylic coatings. As the xylene evaporates more needs to be added to keep the acrylic dissolved (more required in warm conditions).

COVERAGE

To dissolve acrylic sealer, 3-5m² per litre to be expected.

To keep dissolved while the melted product is removed, 1-3m² per litre to be expected.

These guide yields will vary enormously depending on temperature and thickness of acrylic layer to be treated.

PACKAGING

5 & 25 ltr U.N. 1993 approved metal drums.

STORAGE

Store in a cool dry place away from any naked flame or heat source.

HEALTH AND SAFETY

Flammable liquid. Do not smoke. Keep application area well ventilated. Wear respirator when applying. Flash point 42°C (Abel-Closed Cup). Refer to Safety Data Sheet for further information.

TECHNICAL SERVICES

For further information, call our technical dept on:
UK (01635) 202224
International +44(0) 1635 202224

E-Mail:

info@picsuk.com

Website:

www.hatcrete.com

WARRANTY

Pattern Imprinted Concrete Supplies Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst Pattern Imprinted Concrete Supplies Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

MANUFACTURED BY PICS

Unit 2 & 4, Red Shute Hill Ind. Est. Hermitage, Nr Newbury
Berkshire RG18 9QL

Tel: +44 (0) 1635 202224 E-Mail: info@picsuk.com Web: www.hatcrete.com

